

Ethylene Propylene Rubber

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP110 is an EPM rubber with Broad molecular weight distribution, low ethylene contents. It can be used to Heat resistance belt, electircals, Brake part, TPO, adhesives, binder, oil additives, Gasket.	<ul style="list-style-type: none">- Amorphous- Good processing & easy mill handling- Excellent heat resistance

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 1.00	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@100 °C	40.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	52.0 ± 3.5	wt %	ASTM D3900

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag in Mesh Box, LDPE/HDPE film, 900 kg(25 kg × 36)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	12/02/2020
Revision No.	10