

## Ethylene Propylene Rubber

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP2060 is an EPM rubber with broad molecular weight distribution, low ethylene contents, It can be used to TPO, brake parts, Adhesives, electricals and oil additives.	<ul style="list-style-type: none"><li>- Good processing</li><li>- Excellent heat resistance</li><li>- Modification of polyolefin thermoplastics</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	65.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	53.5 ± 4.5	wt %	ASTM D3900

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bale in Mesh Box, LDPE film, 900 kg(25 kg × 36)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	12/02/2020
<b>Revision No.</b>	10