

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP8512 is EPDM grade with very high mooney viscosity, high diene, broad molecular weight distribution and has an excellent processability and physical properties. It can be used to Dense body sealing, Radiator hose, Molded goods, Sponge profiles.	<ul style="list-style-type: none">- High Filler loading & Extrusion processability- Cold resistance at low temperature- Good processability- Improves productivity & collapse resistance

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@150 °C	88.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	55.0 ± 2.0	wt %	ASTM D3900
ENB Contents	8.0 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bale in Carton/Mesh Box, LDPE film, 750 kg(25 kg × 30),
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	07/20/2021
Revision No.	4